



## 1U 19" Single Phase Aluminum 8xFrench with ON/OFF Switch 1,8mt 3x1,5mm<sup>2</sup> Power Cable and 16A French Plug

### DESIGN & MATERIAL

<b>Plastic Material</b>	Fire Retardant Nylon 6 v0 or v2
<b>Body Material</b>	Aluminum Body
<b>Sockets</b>	8xFrench (DIN49441)
<b>Cable Options</b>	1,5 Mtr / <b>1,8 Mtr</b> / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm <sup>2</sup> / 3x2,5 mm <sup>2</sup> / 3x4 mm <sup>2</sup> / 3x6 mm <sup>2</sup>
<b>Rack Mount</b>	19" 1U Rack Mountable
<b>Contacts</b>	Contacts: Brass
<b>Protection</b>	<b>On/Off Switch</b> Circuit Breaker (Brand and Power on Demand) Surge Protect Voltmeter
<b>Certificate</b>	CE
<b>Warranty</b>	Lifetime (On Production Based Errors)

### ELECTRICAL & ENVIROMENTAL

<b>Cable Plug Type Options</b>	<b>UPS (FRENCH-DIN49441)</b> IEC 320 C14) CEE NORM 16A (EN60309) UK 13A (BS1363)
<b>Max. Output power</b>	4000W (220V)
<b>Nominal Input Voltage</b>	100-240VAC
<b>Max. Total Current Draw</b>	16A
<b>Operable Humidity</b>	% 5-95
<b>Operable Temperature</b>	-5°C to +45°C
<b>Storage Temperature</b>	-25°C to +65°C

### Highlights

- 19" Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

### The Package Includes

- PDU
- Screw&Nut Set for installation

### Options

- Surge Protect
- Cable Length/Plug type on demand
- 3/6/9/12 Way Options
- Voltmeter / Ammeter
- Color Options

