



1U 19" Single Phase Aluminum 6xC13 with ON/OFF Switch 1,8mt 3x1,5mm² Power Cable and UPS (DIN49441) Plug

DESIGN & MATERIAL

| | |
|-------------------------|---|
| Plastic Material | Fire Retardant Nylon 6 v0 or v2 |
| Body Material | Aluminum Body |
| Sockets | 6xIEC 320 C13 |
| Cable Options | 1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm² / 3x2,5 mm ² / 3x4 mm ² / 3x6 mm ² |
| Rack Mount | Vertical Rack Mountable |
| Contacts | Contacts: Brass |
| Protection | On/Off Switch 16A Circuit Breaker Surge Protect Voltmeter |
| Certificate | CE |
| Warranty | Lifetime (On Production Based Errors) |

Highlights

- 19" Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

The Package Includes

- PDU
- Screw&Nut Set for installation

Options

- Fixed Plastic Mounting Ear Option
- Cable Length/Plug type on demand
- 3/6/9/12 Way Options
- Voltmeter / Ammeter
- Color Options

ELECTRICAL & ENVIROMENTAL

| | |
|--------------------------------|---|
| Cable Plug Type Options | UPS (DIN49441) IEC 320 C14 CEE NORM 16A (EN60309) UK 13A (BS1363) |
| Max. Output power | 4000W (220V) |
| Nominal Input Voltage | 100-240VAC |
| Max. Total Current Draw | 16A |
| Operable Humidity | % 5-95 |
| Operable Temperature | -5°C to +45°C |
| Storage Temperature | -25°C to +65°C |

