



ZeroU Vertical Single Phase Aluminum 18xUK with Ampermeter 2mt 3x2,5mm² Power Cable and 32A CEE Norm Plug

DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	18xUK
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm ² / 3x2,5 mm² / 3x4 mm ² / 3x6 mm ²
Rack Mount	ZeroU Vertical Rack Mountable
Contacts	Contacts: Phosphor bronze Bus bar: Brass
Protection	Ampermeter On/Off Switch 16A Circuit Breaker Surge Protect
Certificate	CE
Warranty	Lifetime (On Production Based Errors)

Highlights

- 19" Rack Mountable
- Rotating Installation Ears
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

The Package Includes

- PDU
- Screw&Nut Set for installation

Options

- Fixed Plastic Mounting Ear Option
- Cable Length/Plug type on demand
- 3/6/9/12 Way Options
- Voltmeter / Ammeter
- Color Options

ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	CEE NORM 32A (EN60309) UPS (DIN49441) UK 13A (BS1363) IEC 320 C14
Max. Output power	7000W (220V)
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	32A
Operable Humidity	% 5-95
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65°C

