



19" 1U Single Phase Aluminum 8 Schuko Socket 1,8 MT 3x1,5 mm² Cabled UPS Plug Power Distribution Unit (PDU) with ON/OFF Switch

DESIGN & MATERIAL

Plastic Material	Fire Retardant Nylon 6 v0 or v2
Body Material	Aluminum Body
Sockets	8x Schuko Sockets (DIN 49440)
Cable Options	1,5 Mtr / 1,8 Mtr / 2 Mtr / 3 Mtr / 5 Mtr 3x1,5 mm ² / 3x2,5 mm ² / 3x4 mm ² / 3x6 mm ²
Rack Mount	19" 1U Rack Mountable with Plastic Ears
Contacts	Contacts: brass
Protection	ON/OFF Switch Surge Protector 16A Circuit Breaker , Multimeter
Certificate	CE
Warranty	Lifetime (On production based defects)

ELECTRICAL & ENVIROMENTAL

Cable Plug Type Options	UPS(FRENCH DIN49441) CEE NORM 16A (EN60309) UK 13A (BS1363) IEC 320 (C14&C20)
Max. Output power	4000W (220V)
Nominal Input Voltage	100-240VAC
Max. Total Current Draw	16A
Operable Humidity	% 5-95
Operable Temperature	-5°C to +45°C
Storage Temperature	-25°C to +65°C

Highlights

- Rack Mountable
- Aluminum Body
- Fire-retardant plastic material
- Fuse Box designed to prevent accidental shutdowns
- Mounting ears create isolation between rack cabinets and PDU
- Arc flash proof sockets
- 100% Brass socket contacts
- Design Certification

The Package Includes

- PDU
- Screw&Nut Set for installation

Options

- Fixed Plastic Mounting Ear Option
- Cable Length/Plug type on demand
- 3/6/9/12 Way Options
- Voltmeter / Ammeter
- Color Options

