

UPCOM


The Faster. The Better.

www.upcom.com.tr

CONTACTS FOR MAINTNEANCE
AND MANUFACTURING

Istanbul - Turkey


Mail: info@upcom.com.tr
Mob: +90 535 765 18 57
www.upcom.com.tr



Drillfok

DRILLFOK

Drillfok Fiber Optic Cable Blowing Machine



UPCOM MACHINE HISTORY

Our company has been in the machinery and machinery spare parts manufacturing sector since 1994. Since 1999, almost all of the fiber cable blowing works in Turkey have been done using fiber optic cable blowing machines produced by us.

It continues its R&D activities on fiber blowing machines and revisions are made according to customer requests.

Fiber optic cable blowing machines produced by UPCOM are used in many countries of the world, especially in Italy, the Netherlands, Uruguay, Holland, Germany, England, African Countries, Canada, USA, Syria, Iraq, Romain, Bulgaria, Kazakhstan, Libya and Suudi Arabia.

OUR UNDERSTANDING OF QUALITY;

Based on the principle of customer satisfaction first, our focus is to fully perceive customer demands and expectations and provide complete products and services accordingly,

To achieve this goal;

- Continuously improving product quality, reducing costs while increasing product qualities,
- To fully meet technological infrastructure and personnel information needs,
- Aiming for continuous improvement as a whole with the participation of employees.

OUR MISSION

To be the first choice of our customers with our products, solutions, after-sales services, reliability and high business ethics.

OUR VISION

To be a leader in its country and a preferred company in the world with its organization that that makes makes a name for itself in the technological developments in the sector in which it produces products and services, adds value to the lives of its customers and the society in which it operates, is admired

DRILLFOK MACHINE

Drillfok has no internal motor but only external motor such as cordless chargeable drill river. The **Drillfok** installs micro cable with a diameter range of Ø1 to Ø8 mm and up to 1000 m with a speed of 90 m/min depending on your external motor. Its compact design makes your business incredibly easy. The cable blowing system structure ensures a fast and simple change of components for various cable diameter or duct diameters. Ergonomic design and mobility features make the **Drillfok** is ideal for either outside or in-building use. The Drillfok uses compressed air to install the cable. The drive roller, powered by most types of cordless drills-that should be ordered separately-control the microfiber as it is propelled into the micro duct. The **Drillfok** machine takes the name from drilling tool because you do not need to use an internal motor with this machine you only need to use a standard drilling tool.

DRILLFOK CONTENT

CONSIST OF:

- 1set (2pcs) of Rubber Coated Roll
- 1pcs Mechanical Meter Indicator
- 1pcs Head Threaded Drive Shaft

NOT INCLUDING WITH MACHINE:

- Chargeable Drilling Tool
- Lubricant Oil
- Air Compressor

INCLUDING WITH MACHINE:

- 1pcs Operator Guide
- 1pcs Cable Inserts: Options Ø1mm to Ø8mm
- 1set Duct Inserts
- 30pcs Blue Nutring (6pcs per Cable Dia)
- 2m Black Rubber O-Ring
- 1pcs Protected Wooden Case with holder
- 1pcs Quick Insert AirJack



TECHNICAL DATA

Operating with External	Drilling Tool
Micro Duct Diameter (mm)	Ø4 to Ø18
Cable Diameter (mm)	Ø1 to Ø8
Max. Operating Pressure	15 Bar
Meter Indicator	Mechanical
Blowing Direction	Forward & Backward
Quick Connection	Pipe from Compressor
Max. Blowing Distance (m)	1000m
Blowing Speed (m/min)	90 (depends on external motor's speed capacity)
Weight without Package (kg)	6
Weight with Package (kg)	10
Dimensions with Package (cm)	39 x 27 x 33


COMPRESSOR CAPACITY RECOMMENDATION

Ducts upto 8mm – 0,8 m³/min


Ducts upto 8-12mm – 1,0 m³/min

Ducts upto 12-15mm – 1,5 m³/min

These are minimum compressor requirements. You may use higher capacity of compressor which can increase the effectiveness. You can overcome the handicap of improperly installed ducts.



DRILLFOK ACCESSORIES



Drive Rollers (mm)

DR1 : Ø1 - Ø2
DR2 : Ø2,5 - Ø4
DR3 : Ø5 - Ø8

Cable Aligning Parts (mm)

C1 : Ø1 – Ø2
C2 : Ø3 – Ø4
C3 : Ø5 – Ø6
C4 : Ø7 – Ø8

Nutring Seals (mm)

N1 : Ø1
N2 : Ø2 - Ø2,5
N3 : Ø3
N4 : Ø4
N5 : Ø5
N6 : Ø6
N7 : Ø7
N8 : Ø8

Duct Connection Tools (mm)

D1 : Ø4
D2 : Ø8
D3 : Ø10
D4 : Ø12
D5 : Ø14
D6 : Ø16
D7 : Ø18

1 set of Drive Roller Set + 1 set of Cable Aligning Tools + 1 set of Nutring Seals + 1 pcs Duct Connection Tool is included.