


Cat6 SF/UTP

4 pairs / 23 AWG / PVC / 250 MHz



Ø 7.6 mm approx.

SCHEMATIC / NOT TO SCALE

7.60 mm

APPROX. OUTER DIAMETER

62 kg/km

APPROX. CABLE WEIGHT

23 kg/km

COPPER WEIGHT

The four-pair Cat6 core is separated by a cross-shaped spacer and enclosed by foil and tinned copper braid. This 250 MHz construction combines pair separation with two overall screening layers.

CONSTRUCTION

Conductor	Solid annealed copper, 23 AWG
Insulation	Solid polyethylene (PE); EN 50290-2-23
Core assembly	4 twisted pairs around a cross separator
Pair identification	Colour coded to ANSI/TIA-568
Individual pair screen	None
Overall screen	Aluminium/polyester foil + tinned copper braid
Outer jacket	Polyvinyl chloride (PVC); EN 50290-2-22
Jacket colour	RAL 2003 Orange / RAL 7035 Grey; other colours on request

APPLICATION

10BASE-T, 100BASE-TX and 1000BASE-T. IEEE 802.3af / 802.3at (Types 1 and 2).

Link length, connecting hardware and PoE bundle temperature must be checked for the complete installation.

Cat6 SF/UTP

4 pairs / 23 AWG / PVC

ELECTRICAL CHARACTERISTICS / 20°C

Conductor resistance at 20°C	< 85 Ω/km	Delay skew	< 45 ns/100 m
Resistance unbalance	< 1%	Operating voltage	72 V
Insulation resistance, 500 V DC / 1 min	> 5000 MΩ·km	Dielectric test, 1 min	1000 V
Mutual capacitance	50 pF/m	Transverse conversion loss (TCL)	Minimum level 2
Capacitance unbalance	1600 pF/km	Coupling attenuation	Type II
Characteristic impedance at 100 MHz	100 ± 5 Ω	Transfer impedance	Grade 2
Velocity of propagation	67%	Segregation class	c

SELECTED TRANSMISSION CHARACTERISTICS

Frequency MHz	Insertion loss dB / 100 m	NEXT dB	PS NEXT dB	Return loss dB
4	3.6	78	75	32
10	5.7	75	72	25
16	7.2	70	66	25
31.25	10.5	70	64	30
62.5	14.6	60	60	30
100	18.5	60	58	30
250	30	55	52	24

Cable reference values over the stated operating band. Channel performance depends on the installed link.

INSTALLATION AND JACKET

Operating temperature	-20°C to +60°C	PVC-jacketed version for routes specified with a conventional thermoplastic outer sheath. Check the project fire requirement before selecting a jacket.
Minimum bend radius	8 × D / approx. 60.8 mm	
D	Actual cable outer diameter	

Flame propagation reference: IEC/EN 60332-1-2.

Reference specifications: IEC 61156-5, ISO/IEC 11801, EN 50173-1, EN 50288-5-1, ANSI/TIA-568.2-D.

CPR classification and the corresponding Declaration of Performance must be confirmed for the ordered construction.